



E-Control Systems, Inc.

TempNTC – 10WF, TempNTC-11WF,
TempNTC – 20WF, TempNTC – 22WF,
TempNTC – 40WF

IntelliSensor™ for Temperature and Door

IntelliSensor™ Product Description

The IntelliSensor™ is a cost effective, wireless monitoring system operating on the 802.11 b/g Wi-Fi standard for storing and communicating temperature and door status information, among other features. Sensors transmit data wirelessly through any Wi-Fi Infrastructure to our FusionLive™ software, allowing for an easy creation of a centrally managed monitoring application.



IntelliSensor™ Features

- ▶ Battery powered wireless solution operates via Wi-Fi
- ▶ 802.11 b/g compliant
- ▶ Temperature and contact closure (door status) readings
- ▶ Multiple input combinations available in single package (1 to 4 input modules)
- ▶ Completely wireless (No need for power or data cables)
- ▶ Battery lasts up to 3 years
- ▶ Strongest Wi-Fi Transmitter on the market
- ▶ Sensors equipped with data loggers capable of storing up to 1 week-worth of data internally
- ▶ Completely integrated solution with FusionLive™ Software
- ▶ Hardware can be pre-configured at factory (Sensors automatically join network)
- ▶ Firmware can be updated wirelessly (over-the-air)
- ▶ User configurable transmission interval (over-the-air)
- ▶ Conformal coated board for moisture rich operating environments

IntelliSensor™ Specifications

- ▶ Operating temperature of -40 °C to 85 °C
- ▶ Operating humidity of 0 to 100 %, non-condensing
- ▶ 0.1 °C Temperature resolution
- ▶ ± 1 °C Accuracy (± 0.5 °C with calibration)
- ▶ Communication via existing Wi-Fi infrastructure/network
- ▶ Supports DHCP or Static IP
- ▶ WEP, WPA, and WPA2 encryption available



HACCP

